



Safety Data Sheet

LOCTITE LB 8008 C5-A BO 227G

Page 1 of 9

SDS No. : 242144

V001.4

Date of issue: 06.12.2022

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE LB 8008 C5-A BO 227G

Intended use: Antiseize

Supplier:

Henkel Australia Pty Ltd
135-141 Canterbury Road
Kilsyth, Victoria, 3137
Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

<u>Hazard Class</u>	<u>Hazard Category</u>
Skin irritation	Category 2
Serious eye damage/eye irritation	Category 1
Acute hazards to the aquatic environment	Category 2
Chronic hazards to the aquatic environment	Category 3

Hazard pictogram:



Signal word:

Danger

Hazard statement(s): H315 Causes skin irritation.
H318 Causes serious eye damage.
H401 Toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention: P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves, eye protection, and face protection.

Response: P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338+P315 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Get immediate medical advice/attention.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO	64742-52-5	10- < 30 %
Calcium dihydroxide	1305-62-0	10- < 20 %
Copper	7440-50-8	10- < 30 %
Graphite	7782-42-5	< 10 %
Quartz (SiO2) "respirable particulates (reaches the alveoli)" (RCS) <0.1%	14808-60-7	< 10 %
non hazardous ingredients~		30- <= 60 %

Section 4. First aid measures

Ingestion: Rinse mouth, do not induce vomiting, consult a doctor.

Skin: Rinse with running water and soap.
Seek medical advice.

Eyes: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

First Aid facilities: Eye wash
Normal washroom facilities

Medical attention and special treatment: Treat symptomatically and supportively.

Section 5. Fire fighting measures

- Suitable extinguishing media:** Carbon dioxide, foam, powder
- Improper extinguishing media:** High pressure waterjet
- Decomposition products in case of fire:** Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
- Special protective equipment for fire-fighters:** Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Section 6. Accidental release measures

- Personal precautions:** Avoid contact with skin and eyes.
See advice in section 8
- Environmental precautions:** Do not empty into drains / surface water / ground water.
- Clean-up methods:** Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

- Precautions for safe handling:** Do not inhale vapors and fumes.
Use only in well-ventilated areas.
Refer to Section 8.
- Conditions for safe storage:** Store at room temperature.

Section 8. Exposure controls / personal protection

National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
Oil mist, refined mineral 64742-52-5			5				
CALCIUM HYDROXIDE 1305-62-0			5				
COPPER, DUSTS & MISTS (AS CU) 7440-50-8	Dust and mist.		1				
COPPER (FUME) 7440-50-8	Fume.		0.2				
GRAPHITE (ALL FORMS EXCEPT FIBRES) (RESPIRABLE DUST) (NATURAL & SYNTHETIC) 7782-42-5	Respirable dust.		3				
SILICA, CRYSTALLINE: QUARTZ (RESPIRABLE DUST) 14808-60-7	Respirable dust.		0.05				
QUARTZ (RESPIRABLE DUST) 14808-60-7	Respirable dust.		0.05				

Engineering controls:	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.
Eye protection:	Tightly fitting safety goggles
Skin protection:	Use of an impervious apron is recommended. Nitrile rubber gloves should be worn.
Respiratory protection:	If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance:	Copper Paste
Odor:	mild
pH:	Not applicable, Product is non-soluble (in water).
Melting point / freezing point:	Not applicable
Specific gravity:	1.30
Boiling point:	> 260 °C (> 500 °F)
Flash point:	> 93 °C (> 199.4 °F)
Vapor pressure:	< 0.6 mbar (None)
Vapor density:	Heavier than air.
Density:	1.3 g/cm ³
Auto ignition:	Not determined
Decomposition temperature:	
VOC content (2004/42/EC)	0 % (VOCV 814.018 VOC regulation CH)

Section 10. Stability and reactivity

Stability:	Stable under normal conditions of temperature and pressure.
Conditions to avoid:	Avoid excessive heat and ignition sources.
Incompatible materials:	Reaction with strong acids. Oxidizing agents.
Hazardous decomposition products:	In case of fire toxic gases can be released. carbon oxides.

Section 11. Toxicological information

Health Effects:

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Principal hazard of ingestion is aspiration into the lungs and subsequent pneumonitis.

Skin: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Eyes: Causes serious eye damage. Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Inhalation: May cause respiratory tract irritation. Inhalation of copper fumes may result in metal fume fever. Symptoms include metallic taste, discoloration of skin or hair.

Aggravated med. condition: Eye, skin, and respiratory disorders.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	LD50 LC50 LD50	> 5,000 mg/kg > 5.53 mg/l > 5,000 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
Calcium dihydroxide 1305-62-0	LD50 LD50	> 7,340 mg/kg > 2,500 mg/kg	oral dermal		rat rat	OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
Copper 7440-50-8	LD50 LC50 LD50	> 2,500 mg/kg > 5.11 mg/l > 2,000 mg/kg	oral inhalation dermal	4 h	rat rat rat	OECD Guideline 423 (Acute Oral toxicity) OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class (ATC) Method) OECD Guideline 402 (Acute Dermal Toxicity)
Graphite 7782-42-5	Acute toxicity estimate (ATE) LC50	> 5,000 mg/kg > 2 mg/l	oral inhalation	4 h	rat	Expert judgement OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Calcium dihydroxide 1305-62-0	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Copper 7440-50-8	not irritating		rabbit	EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion)
Graphite 7782-42-5	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Calcium dihydroxide 1305-62-0	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Copper 7440-50-8	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Graphite 7782-42-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Copper 7440-50-8	not sensitising	Guinea pig maximisation test	guinea pig	EU Method B.6 (Skin Sensitisation)
Graphite 7782-42-5	not sensitising	Mouse local lymph node assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Calcium dihydroxide 1305-62-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Copper 7440-50-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Copper 7440-50-8	negative negative	oral: gavage oral: gavage		mouse rat	EU Method B.12 (Mutagenicity equivalent or similar to OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Graphite 7782-42-5	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Copper 7440-50-8	NOAEL=1000 ppm	oral: feed	92 d7 d/w	rat	EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Graphite 7782-42-5	NOAEL=ca. 813 mg/kg	oral: feed	daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Section 12. Ecological information

General ecological information: Do not empty into drains / surface water / ground water.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	LC50	> 1,000 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	EC50	> 1,000 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	NOELR	100 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium dihydroxide 1305-62-0	LC50	50.6 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Calcium dihydroxide 1305-62-0	EC50	49.1 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Calcium dihydroxide 1305-62-0	EC50	184.57 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium dihydroxide 1305-62-0	NOEC	48 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Calcium dihydroxide 1305-62-0	EC20	229.2 mg/l	Bacteria	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) other guideline:
Copper 7440-50-8	LC50	0.193 mg/l	Fish	96 h	Pimephales promelas	
Copper 7440-50-8	NOEC	0.188 mg/l	Fish	30 d	Perca fluviatilis	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
Copper 7440-50-8	EC50	> 0.1 - 1 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Copper 7440-50-8	EC50	> 0.1 - 1 mg/l	Algae	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Copper 7440-50-8	NOEC	> 0.1 - 1 mg/l	Algae	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Copper 7440-50-8	EC50	> 0.1 - 1 mg/l	Bacteria	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Graphite 7782-42-5	LC50	> 10,000 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Graphite 7782-42-5	EC50	> 5,600 mg/l	Daphnia	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
---------------------------------	--------	-------------------------	---------------	--------

Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	not readily biodegradable.	aerobic	6 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
--	----------------------------	---------	-----	---

Section 13. Disposal considerations

- Waste disposal of product:** Collection and delivery to recycling enterprise or other registered elimination institution.
- Recommended cleanser:** Suitable organic solvents:
- Disposal for uncleaned package:** Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Marine transport IMDG:

UN no.: 3082
 Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Copper)
 Class or division: 9
 Packing group: III
 EmS: F-A ,S-F
 Seawater pollutant: Marine pollutant

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

- SUSMP Poisons Schedule** None
- AIC:** All components are listed or are exempt from listing on the Australian Inventory of Industrial Chemicals or Introduced under AICIS.

Section 16. Other information

- Abbreviations/acronyms:** AIIC - Australian Inventory of Industrial Chemicals (AIIC)
AICIS - Australian Industrial Chemicals Introduction Scheme
- Reason for issue:** Reviewed SDS. Reissued with new date. involved chapters: 1 - 16

Date of previous issue: 14.11.2019

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.