

# HIT-RE 500 V3

## Safety information for 2-Component-products

Issue date: 13/05/2020

Revision date: 13/05/2020

Supersedes: 25/02/2019

Version: 2.3

### SECTION 1: Kit identification

#### 1.1 Product identifier

Product name

HIT-RE 500 V3



Product code

BU Anchor

#### 1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti, Inc.  
Legacy Tower, Suite 1000  
7250 Dallas Parkway  
TX 75024 Plano - USA  
T +1 9724035800  
1-800-879-8000 toll free - F +1 918 254 0522

### SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

### SECTION 3: Kit contents

#### Classification of the Product

##### GHS-US classification

Skin Corr. 1B	H314 - Causes severe skin burns and eye damage.
Skin Sens. 1	H317 - May cause an allergic skin reaction.
Muta. 2	H341 - Suspected of causing genetic defects.
Repr. 1B	H360 - May damage fertility or the unborn child.
STOT SE 3	H335 - May cause respiratory irritation.

#### Label elements

##### GHS US labelling

Hazard pictograms (GHS US)



GHS05

GHS07

GHS08

Signal word (GHS US)

Danger

Hazardous ingredients

Epoxy resin, Amines

Hazard statements (GHS US)

Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.  
May cause respiratory irritation.  
Suspected of causing genetic defects.  
May damage fertility or the unborn child.

Precautionary statements (GHS US)

Wear eye protection, protective clothing, protective gloves.  
Do not get in eyes, on skin, or on clothing.


# HIT-RE 500 V3

## Safety information for 2-Component-products

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 If on skin: Wash with plenty of water.

### Additional information

2-component-foilpack, contains:  
 Component A: Epoxy resin, Reactive diluent, inorganic filler  
 Component B: Amine hardener, inorganic filler



Name	General description	Quantity	Unit	GHS-US classification
HIT-RE 500 V3, B		1	pcs (pieces)	Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335
HIT-RE 500 V3, A		1	pcs (pieces)	Skin Corr. 1C, H314 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360

### SECTION 4: General advice

General advice For professional users only

### SECTION 5: Safe handling advice

General measures	Spilled material may present a slipping hazard
Environmental precautions	Prevent entry to sewers and public waters Notify authorities if liquid enters sewers or public waters Avoid release to the environment Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.
Storage conditions	Protect from sunlight. Store in a well-ventilated place.
Technical measures	Comply with applicable regulations
Precautions for safe handling	Wear personal protective equipment Avoid contact with skin and eyes Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work Avoid contact during pregnancy/while nursing
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation Mechanically recover the product On land, sweep or shovel into suitable containers Store away from other materials.
For containment	Collect spillage.
Incompatible materials	Sources of ignition Direct sunlight
Incompatible products	Strong bases Strong acids

### SECTION 6: First aid measures

First-aid measures after eye contact Get immediate medical advice/attention.

# HIT-RE 500 V3

## Safety information for 2-Component-products

---

First-aid measures after ingestion	Immediately rinse with water for a prolonged period while holding the eyelids wide open Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist
First-aid measures after inhalation	Do not induce vomiting
First-aid measures after skin contact	Rinse mouth Immediately call a POISON CENTER/doctor. Remove person to fresh air and keep comfortable for breathing.
First-aid measures general	Wash with plenty of water/... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
Symptoms/effects	Never give anything by mouth to an unconscious person
Symptoms/effects after eye contact	If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects after inhalation	Causes severe skin burns and eye damage. Causes serious eye damage. May cause an allergic skin reaction.

### **SECTION 7: Fire fighting measures**

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

### **SECTION 8: Other information**

No data available

# HIT-RE 500 V3, B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 05/13/2020

Revision date: 05/13/2020

Supersedes: 02/25/2019

Version: 1.4

### SECTION 1: Identification

#### 1.1. Identification

Product form	Mixture
Product name	HIT-RE 500 V3, B
Product code	BU Anchor

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	Composite mortar component for fasteners in the construction industry
------------------------------	---

#### 1.3. Details of the supplier of the safety data sheet

**Supplier**

Hilti, Inc.  
Legacy Tower, Suite 1000  
7250 Dallas Parkway  
TX 75024 Plano - USA  
T +1 9724035800  
1-800-879-8000 toll free - F +1 918 254 0522

**Department issuing data specification sheet**

Hilti Entwicklungsgesellschaft mbH  
Hiltistraße 6  
86916 Kaufering - Deutschland  
T +49 8191 906876  
[anchor.hse@hilti.com](mailto:anchor.hse@hilti.com)

#### 1.4. Emergency telephone number

Emergency number	Chem-Trec Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada) Tel.: 703 527 3887 (Other countries) +1 918 8723000 1-800-879-8000 toll free
------------------	---

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**GHS-US classification**

Skin Corr. 1B H314 - Causes severe skin burns and eye damage.  
Skin Sens. 1 H317 - May cause an allergic skin reaction.  
STOT SE 3 H335 - May cause respiratory irritation.

Full text of H statements : see section 16

#### 2.2. Label elements

**GHS US labelling**

Hazard pictograms (GHS US)



GHS05

GHS07

Signal word (GHS US)

Danger

Hazard statements (GHS US)

H314 - Causes severe skin burns and eye damage.  
H317 - May cause an allergic skin reaction.  
H335 - May cause respiratory irritation.

Precautionary statements (GHS US)

P280 - Wear eye protection, protective clothing, protective gloves.  
P262 - Do not get in eyes, on skin, or on clothing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.

# HIT-RE 500 V3, B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P302+P352 - If on skin: Wash with plenty of water.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
2-methyl-1,5-pentanediamine	(CAS-No.) 15520-10-2	25 - 35	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335
Quartz (SiO <sub>2</sub> )		10 - 25	Carc. 1A, H350
Phenol, styrenated	(CAS-No.) 61788-44-1	5 - 10	Skin Irrit. 2, H315 Skin Sens. 1, H317
m-Xylylenediamine	(CAS-No.) 1477-55-0	5 - <8	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2	1 - 2,5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319
3-Aminopropyltriethoxysilan	(CAS-No.) 919-30-2	1 - 2,5	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/.... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist.
First-aid measures after ingestion	Do not induce vomiting. Rinse mouth. Immediately call a POISON CENTER/doctor.

### 4.2. Most important symptoms and effects (acute and delayed)

Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye damage.

# HIT-RE 500 V3, B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.3. Immediate medical attention and special treatment, if necessary

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Reactivity	Corrosive vapours.
------------	--------------------

### 5.3. Advice for firefighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

#### 6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.
----------------------	---------------------------------

#### 6.1.2. For emergency responders

Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

### 6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact during pregnancy/while nursing.
-------------------------------	---

# HIT-RE 500 V3, B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	Comply with applicable regulations.
Storage conditions	Protect from sunlight. Store in a well-ventilated place.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	41 - 77 °F
Heat and ignition sources	Keep away from heat and direct sunlight.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

HIT-RE 500 V3, B		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (R - Respirable particulate matter)
ACGIH	Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable fraction)
2-methyl-1,5-pentanediamine (15520-10-2)		
Not applicable		
Phenol, styrenated (61788-44-1)		
Not applicable		
m-Xylylenediamine (1477-55-0)		
ACGIH	ACGIH Ceiling (ppm)	0.018 ppm
ACGIH	Remark (ACGIH)	Eye, skin, & GI irr
3-Aminopropyltriethoxysilan (919-30-2)		
Not applicable		
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)		
Not applicable		
Quartz (SiO <sub>2</sub> )		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (Respirable fraction)
ACGIH	Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
OSHA	Remark (OSHA)	(3) See Table Z-3.

Additional information

The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

### 8.2. Exposure controls

Appropriate engineering controls  
Personal protective equipment

Ensure good ventilation of the work station.  
Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.



Materials for protective clothing

Long sleeved protective clothing.

# HIT-RE 500 V3, B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hand protection	Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.
Eye protection	Wear security glasses which protect from splashes.
Skin and body protection	Wear suitable protective clothing.
Environmental exposure controls	No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.
Consumer exposure controls	Avoid contact during pregnancy/while nursing.
Other information	Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	red
Odour	Amine-like
Odour threshold	No data available
pH	11.5
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Relative evaporation rate (butylacetate=1)	No data available
Flammability (solid, gas)	No data available
Explosive limits	No data available
Explosive properties	No data available
Oxidising properties	No data available
Vapour pressure	No data available
Relative density	No data available
Relative vapour density at 20 °C	No data available
Density	1.31 g/cm <sup>3</sup>
Solubility	insoluble in water.
Log Pow	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	50 - 70 Pa·s HN-0333

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Corrosive vapours.

### 10.2. Chemical stability

Stable under normal conditions.



# HIT-RE 500 V3, B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.3. Possibility of hazardous reactions

No additional information available.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide. Corrosive vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity

Not classified

<b>2-methyl-1,5-pentanediamine (15520-10-2)</b>	
LD50 oral rat	1690 mg/kg (Rat)
LD50 dermal rat	1870 mg/kg
LC50 inhalation rat (mg/l)	4.9 mg/l
ATE US (oral)	1690 mg/kg bodyweight
ATE US (dermal)	1870 mg/kg bodyweight
ATE US (vapours)	4.9 mg/l/4h
ATE US (dust,mist)	4.9 mg/l/4h
<b>Phenol, styrenated (61788-44-1)</b>	
LD50 oral rat	> 2500 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	158.31 mg/l/4h
ATE US (vapours)	158.31 mg/l/4h
ATE US (dust,mist)	158.31 mg/l/4h
<b>m-Xylylenediamine (1477-55-0)</b>	
LD50 oral rat	1090 mg/kg
LD50 dermal rat	> 3100 mg/kg
ATE US (oral)	660 mg/kg bodyweight
ATE US (dust,mist)	1.34 mg/l/4h
<b>3-Aminopropyltriethoxysilan (919-30-2)</b>	
LD50 oral rat	1.57 ml/kg
ATE US (oral)	1570 mg/kg bodyweight
<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
LD50 oral rat	2169 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 2169 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Literature study; Other; >1 ml/kg; Rat; Experimental value)
ATE US (oral)	500 mg/kg bodyweight

Skin corrosion/irritation

Causes severe skin burns and eye damage.

pH: 11.5

Serious eye damage/irritation

Serious eye damage, category 1, implicit

pH: 11.5

Respiratory or skin sensitisation

May cause an allergic skin reaction.

# HIT-RE 500 V3, B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
Carcinogenicity	Not classified

Quartz (SiO <sub>2</sub> )	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	Not classified Based on available data, the classification criteria are not met
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye damage.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - water Harmful to aquatic life with long lasting effects.

2-methyl-1,5-pentanediamine (15520-10-2)	
LC50 fish 1	130 mg/l (LC50; 48 h)
LOEC (acute)	1800 mg/l
NOEC (acute)	1000 mg/l
Phenol, styrenated (61788-44-1)	
LC50 fish 1	5.6 mg/l
LC50 other aquatic organisms 1	9.7 mg/l
EC50 Daphnia 1	1.44 mg/l
NOEC (acute)	3.2 mg/l
Threshold limit algae 1	0.326 mg/l (72 h; Algae)
Threshold limit algae 2	0.14 mg/l (72 h; Algae)
m-Xylylenediamine (1477-55-0)	
LC50 fish 1	75 mg/l
LC50 other aquatic organisms 1	20.3 ppb
EC50 Daphnia 1	15 mg/l
LOEC (chronic)	15 mg/l
NOEC (acute)	10.5 mg/kg
NOEC (chronic)	4.7 mg/l
NOEC chronic crustacea	4.7 mg/l
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LC50 fish 1	> 100 mg/l (96 h; Pisces; Nominal concentration)
EC50 Daphnia 1	10 - 100 mg/l (Invertebrata; Estimated value)
EC50 other aquatic organisms 1	84 mg/l (72 h; Desmodesmus subspicatus; growth rate; ECHA)
LC50 fish 2	70.9 mg/l (96 h; Pisces)
ErC50 (algae)	84 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
NOEC (chronic)	2 mg/l (28 d; activated sludge, domestic; respiration rate; ECHA)



# HIT-RE 500 V3, B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	RID
<b>14.1. UN number</b>			
3259	3259	3259	3259
<b>14.2. UN proper shipping name</b>			
AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)
<b>Transport document description</b>			
UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II, (E)	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II
<b>14.3. Transport hazard class(es)</b>			
8	8	8	8
<b>14.4. Packing group</b>			
II	II	II	II
<b>14.5. Environmental hazards</b>			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available			

#### 14.6. Special precautions for user

##### - Overland transport

Classification code (ADR)	C8
Special provisions (ADR)	274
Limited quantities (ADR)	1kg
Packing instructions (ADR)	P002, IBC08
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	2

# HIT-RE 500 V3, B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Orange plates



Tunnel restriction code (ADR)

E

### - Transport by sea

Special provisions (IMDG)	274
Limited quantities (IMDG)	1 kg
Packing instructions (IMDG)	P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A
Stowage and segregation (IMDG)	Separated from acids.
MFAG-No	154

### - Air transport

PCA packing instructions (IATA)	859
PCA max net quantity (IATA)	15kg
CAO packing instructions (IATA)	863
Special provisions (IATA)	A3

### - Rail transport

Special provisions (RID)	274
Limited quantities (RID)	1kg
Packing instructions (RID)	P002, IBC08
Carriage prohibited (RID)	No

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

#### CANADA

No additional information available

<b>m-Xylylenediamine (1477-55-0)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>
Listed on the Canadian DSL (Domestic Substances List)

<b>Quartz (SiO<sub>2</sub>)</b>
Listed on the Canadian DSL (Domestic Substances List)

# HIT-RE 500 V3, B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### EU-Regulations

No additional information available

### National regulations

#### Quartz (SiO<sub>2</sub>)

Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
2-methyl-1,5-pentanediamine(15520-10-2)	
Phenol, styrenated(61788-44-1)	
m-Xylylenediamine(1477-55-0)	
3-Aminopropyltriethoxysilan(919-30-2)	
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Quartz (SiO <sub>2</sub> )()	

## SECTION 16: Other information

Revision date

05/13/2020

Abbreviations and acronyms

European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. European Agreement concerning the International Carriage of Dangerous Goods by Road. Acute Toxicity Estimate. Bioconcentration factor. Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008. Derived Minimal Effect level. Derived-No Effect Level. International Air Transport Association. Median effective concentration. International Maritime Dangerous Goods. Median lethal concentration. Median lethal dose. Lowest Observed Adverse Effect Level. No-Observed Adverse Effect Concentration. No-Observed Adverse Effect Level. No-Observed Effect Concentration. Persistent Bioaccumulative Toxic. Predicted No-Effect Concentration. Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. Regulations concerning the International Carriage of Dangerous Goods by Rail. Safety Data Sheet. Very Persistent and Very Bioaccumulative.

Other information

None.

# HIT-RE 500 V3, B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-statements:

H227	Combustible liquid
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H412	Harmful to aquatic life with long lasting effects.

NFPA health hazard


3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard

1 - Materials that must be preheated before ignition can occur.

NFPA reactivity

0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health

3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability

1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical

0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection

B  
B - Safety glasses, Gloves

Indication of changes:

Section	Changed item	Change	Comments
2.1	GHS-US classification		
3	Composition/information on ingredients	Modified	

SDS\_US\_Hilti

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

# HIT-RE 500 V3, A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 05/13/2020

Revision date: 05/13/2020

Supersedes: 02/25/2019

Version: 2.3

### SECTION 1: Identification

#### 1.1. Identification

Product form	Mixture
Product name	HIT-RE 500 V3, A
Product code	BU Anchor

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	Composite mortar component for fasteners in the construction industry
------------------------------	---

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Hilti, Inc.  
Legacy Tower, Suite 1000  
7250 Dallas Parkway  
TX 75024 Plano - USA  
T +1 9724035800  
1-800-879-8000 toll free - F +1 918 254 0522

##### Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH  
Hiltistraße 6  
86916 Kaufering - Deutschland  
T +49 8191 906876  
[anchor.hse@hilti.com](mailto:anchor.hse@hilti.com)

#### 1.4. Emergency telephone number

Emergency number	Chem-Trec Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada) Tel.: 703 527 3887 (Other countries) +1 918 8723000 1-800-879-8000 toll free
------------------	---

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Skin Corr. 1C	H314 - Causes severe skin burns and eye damage.
Skin Sens. 1	H317 - May cause an allergic skin reaction.
Muta. 2	H341 - Suspected of causing genetic defects.
Repr. 1B	H360 - May damage fertility or the unborn child.

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS US labelling

Hazard pictograms (GHS US)



GHS05

GHS07

GHS08

Signal word (GHS US)

Danger

Hazard statements (GHS US)

H314 - Causes severe skin burns and eye damage.  
H317 - May cause an allergic skin reaction.  
H341 - Suspected of causing genetic defects.  
H360 - May damage fertility or the unborn child.

Precautionary statements (GHS US)

P280 - Wear eye protection, protective clothing, protective gloves.  
P262 - Do not get in eyes, on skin, or on clothing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



# HIT-RE 500 V3, A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
 P337+P313 - If eye irritation persists: Get medical advice/attention.  
 P302+P352 - If on skin: Wash with plenty of water.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Quartz (SiO <sub>2</sub> )		25 - 40	Carc. 1A, H350
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	(CAS-No.) 1675-54-3	25 - 40	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	(CAS-No.) 9003-36-5	10-20	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
butanedioldiglycidyl ether	(CAS-No.) 2425-79-8	5 - 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317
trimethylolpropane triglycidylether	(CAS-No.) 30499-70-8	5 - 10	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Muta. 2, H341 Repr. 1B, H360 Aquatic Chronic 2, H411
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8	2.5 - 5	Eye Dam. 1, H318

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Gently wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after skin contact	Causes skin irritation.
Symptoms/effects after eye contact	Causes serious eye irritation.

# HIT-RE 500 V3, A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.3. Immediate medical attention and special treatment, if necessary

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
<b>6.1.1. For non-emergency personnel</b>	
Emergency procedures	Evacuate unnecessary personnel.
<b>6.1.2. For emergency responders</b>	
Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

### 6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
-------------------------------	---

# HIT-RE 500 V3, A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	41 - 77 °F
Heat and ignition sources	Keep away from heat and direct sunlight.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

HIT-RE 500 V3, A		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (R - Respirable particulate matter)
ACGIH	Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Quartz (SiO <sub>2</sub> )		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (Respirable fraction)
ACGIH	Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
OSHA	Remark (OSHA)	(3) See Table Z-3.
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)		
Not applicable		
butanedioldiglycidyl ether (2425-79-8)		
Not applicable		
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)		
Not applicable		
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)		
Not applicable		
trimethylolpropane triglycidylether (30499-70-8)		
Not applicable		

Additional information

The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.

### 8.2. Exposure controls

Appropriate engineering controls  
Personal protective equipment

No specific measures identified.  
Safety glasses. Gloves. Protective clothing. Avoid all unnecessary exposure.



Materials for protective clothing  
Hand protection

Long sleeved protective clothing.  
Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Eye protection

Wear security glasses which protect from splashes.

Skin and body protection

Wear suitable protective clothing.

# HIT-RE 500 V3, A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Environmental exposure controls	No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.
Consumer exposure controls	Avoid contact during pregnancy/while nursing.
Other information	Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Light grey
Odour	characteristic
Odour threshold	No data available
pH	6.6
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Relative evaporation rate (butylacetate=1)	No data available
Flammability (solid, gas)	No data available
Explosive limits	No data available
Explosive properties	No data available
Oxidising properties	No data available
Vapour pressure	No data available
Relative density	No data available
Relative vapour density at 20 °C	No data available
Density	1.45 g/cm <sup>3</sup>
Solubility	insoluble in water.
Log Pow	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	45 - 59 Pa·s 23 °C

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No additional information available.

# HIT-RE 500 V3, A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity Not classified

<b>Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight (Rat; ECHA)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; ECHA)
<b>butanedioldiglycidyl ether (2425-79-8)</b>	
LD50 oral rat	2980 mg/kg (Rat)
LD50 dermal rabbit	1130 mg/kg (Rabbit)
ATE US (oral)	1163 mg/kg bodyweight
ATE US (dermal)	1130 mg/kg bodyweight
ATE US (gases)	4500 ppmv/4h
ATE US (vapours)	11 mg/l/4h
ATE US (dust,mist)	1.5 mg/l/4h
<b>[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)</b>	
LD50 oral rat	8025 mg/kg bodyweight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	4250 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
ATE US (oral)	8025 mg/kg bodyweight
ATE US (dermal)	4250 mg/kg bodyweight
<b>2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)</b>	
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)

Skin corrosion/irritation	Causes severe skin burns and eye damage. pH: 6.6
Serious eye damage/irritation	Serious eye damage, category 1, implicit pH: 6.6
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Suspected of causing genetic defects.
Carcinogenicity	Not classified

<b>Quartz (SiO2)</b>	
IARC group	1 - Carcinogenic to humans

<b>2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)</b>	
IARC group	3 - Not classifiable

Reproductive toxicity	May damage fertility or the unborn child.
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified

# HIT-RE 500 V3, A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	No additional information available.
Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after skin contact	Causes skin irritation.
Symptoms/effects after eye contact	Causes serious eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - water Toxic to aquatic life with long lasting effects.

<b>butanedioldiglycidyl ether (2425-79-8)</b>	
LC50 fish 1	24 mg/l (96 h; Pisces) ECHA
LC50 other aquatic organisms 1	> 160 mg/l
NOEC (acute)	40 mg/l
Threshold limit algae 1	88930 mg/l (96 h; Algae)

<b>[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)</b>	
LC50 fish 1	55 mg/l (96 h; Cyprinus carpio; Young)
EC50 Daphnia 1	473 - 710 mg/l (48 h; Daphnia magna)
LC50 fish 2	237 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
Threshold limit algae 1	119 mg/l (7 days; Anabaena flosaquae)
Threshold limit algae 2	250 mg/l (72 h; Selenastrum capricornutum)

<b>2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)</b>	
LC50 fish 1	2.3 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	2 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
LC50 fish 2	2.3 mg/l (96 h; Oncorhynchus mykiss; Nominal concentration)
Threshold limit algae 1	> 11 mg/l (72 h; Scenedesmus sp.)
Threshold limit algae 2	4.2 mg/l (72 h; Scenedesmus sp.)

### 12.2. Persistence and degradability

<b>HIT-RE 500 V3, A</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.

<b>Quartz (SiO2)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

<b>butanedioldiglycidyl ether (2425-79-8)</b>	
Biochemical oxygen demand (BOD)	0.01982 g O <sub>2</sub> /g substance

<b>2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)</b>	
Persistence and degradability	Not readily biodegradable in water.

### 12.3. Bioaccumulative potential

<b>HIT-RE 500 V3, A</b>	
Bioaccumulative potential	Not established.

<b>Quartz (SiO2)</b>	
Bioaccumulative potential	No bioaccumulation data available.



# HIT-RE 500 V3, A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ADR	IMDG	IATA	RID
<b>14.3. Transport hazard class(es)</b>			
8	8	8	8
<b>14.4. Packing group</b>			
III	III	III	III
<b>14.5. Environmental hazards</b>			
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available			

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR)	C10
Special provisions (ADR)	274
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3
Orange plates	

Tunnel restriction code (ADR)

E

#### - Transport by sea

Special provisions (IMDG)	223, 274
Packing instructions (IMDG)	P002, LP02
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A

#### - Air transport

PCA packing instructions (IATA)	860
PCA max net quantity (IATA)	25kg
CAO packing instructions (IATA)	864
Special provisions (IATA)	A3, A803

#### - Rail transport

Special provisions (RID)	274
Packing instructions (RID)	P002, IBC08, LP02, R001
Carriage prohibited (RID)	No

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code



# HIT-RE 500 V3, A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
butanedioldiglycidyl ether (2425-79-8)	
EPA TSCA Regulatory Flag	TP - TP - indicates a substance that is the subject of a proposed TSCA section 4 test rule.
trimethylolpropane triglycidylether (30499-70-8)	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

#### 15.2. International regulations

##### CANADA

Quartz (SiO <sub>2</sub> )
Listed on the Canadian DSL (Domestic Substances List)
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)
Listed on the Canadian DSL (Domestic Substances List)
butanedioldiglycidyl ether (2425-79-8)
Listed on the Canadian DSL (Domestic Substances List)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)
Listed on the Canadian DSL (Domestic Substances List)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)
Listed on the Canadian DSL (Domestic Substances List)

##### EU-Regulations

No additional information available

##### National regulations

Quartz (SiO <sub>2</sub> )
Listed on IARC (International Agency for Research on Cancer)

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
butanedioldiglycidyl ether (2425-79-8)	

# HIT-RE 500 V3, A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane(1675-54-3)	
trimethylolpropane triglycidylether(30499-70-8)	
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane(2530-83-8)	
Quartz (SiO <sub>2</sub> )(I)	

### SECTION 16: Other information

Revision date	05/13/2020
Abbreviations and acronyms	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. European Agreement concerning the International Carriage of Dangerous Goods by Road. Acute Toxicity Estimate. Bioconcentration factor. Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008. Derived Minimal Effect level. Derived-No Effect Level. International Air Transport Association. Median effective concentration. International Maritime Dangerous Goods. Median lethal concentration. Median lethal dose. Lowest Observed Adverse Effect Level. No-Observed Adverse Effect Concentration. No-Observed Adverse Effect Level. No-Observed Effect Concentration. Persistent Bioaccumulative Toxic. Predicted No-Effect Concentration. Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. Regulations concerning the International Carriage of Dangerous Goods by Rail. Safety Data Sheet. Very Persistent and Very Bioaccumulative.
Other information	None.

#### Full text of H-statements:

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H360	May damage fertility or the unborn child.
H411	Toxic to aquatic life with long lasting effects.

NFPA health hazard


3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard

1 - Materials that must be preheated before ignition can occur.

NFPA reactivity

0 - Material that in themselves are normally stable, even under fire conditions.





# HIT-RE 500 V3, A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Hazard Rating

Health 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Personal protection  
B  
B - Safety glasses, Gloves

### Indication of changes:

Section	Changed item	Change	Comments
9	pH	Added	
14	Transportation information	Modified	
16	Additional information	Added	

SDS\_US\_Hilti

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*