



SOLDER SEAL LIQUID WRENCH NO. 1 (POUR)

MSDS Number

BXTML

National Stock Number

9150-00-261-7899

Product Name

SOLDER SEAL LIQUID WRENCH NO. 1 (POUR)

Manufacturer

RADIATOR SPECIALTY COMPANY

Product Identification

Product ID: SOLDER SEAL LIQUID WRENCH NO. 1 (POUR)

MSDS Date: 08/01/1994

FSC: 9150

NIIN: 00-261-7899

MSDS Number: BXTML

Responsible Party

RADIATOR SPECIALTY COMPANY

1400 W. INDEPENDENCE BLVD.

CHARLOTTE , NC 28208

US

Emergency Phone: 704-377-6555

Info Phone: 704-377-6555

Preparer: I. LIEBMAN

Cage: 77628

Contractor

RADIATOR SPECIALTY COMPANY

34689

CHARLOTTE, NC 28208

US

704-377-6555/303-623-5716

Cage: 77628

Ingredients

ALIPHATIC PETROLEUM SOLVENT

CAS: 8008-20-6

RTECS: OA5500000

Fraction By Weight: 89-90%

ACGIH TLV: 100 PPM (AIR)

PETROLEUM MINERAL OIL

CAS: 64742-06-9

Fraction By Weight: 9-11%

ACGIH TLV: 5 MG/M3

Hazards



Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: IRRITANT. SKIN: IRRITANT.
PROLONGED EXPOSURE CAN CAUSE DERMATITIS. INGESTION: HARMFUL OR
FATAL IF SWALLOWED! ASPIRATION CAN LEAD TO LUNG IRRITATION.
Explanation of Carcinogenicity:NONE.
Effects of Overexposure:INHALATION-EXCESSIVE INHALATION CAN CAUSE
DIZZINESS, RESPIRATORY AND LUNG IRRITATION. INGESTION-CAN CAUSE
GASTRIC DISTURBANCES, NAUSEA.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:EYE: FLUSH W/WATER 15 MINS, LIFTING LIDS. IF ADVERSE EFFECTS
PERSIST-GET MED ATTN IMMED. SKIN: WASH W/SOAP AND WATER. REMOVE
CONTAMINATED CLOTHING AND LAUNDER BEFORE RE-USE. INHAL: REMOVE TO
FRESH AIR . IF BREATHING DIFFICULT-ADMINISTER OXYGEN, IF
STOPPED-APPLY ARTIFICIAL RESPIRATION. GET MED ATTN. INGEST: DO NOT
INDUCE VOMITING! GET MED ATTN IMMED. DO NOT ADMINISTER EPINEPHRINE
OR ADRENALIN!!

Fire Fighting

Flash Point Method:TCC
Flash Point:132F,56C
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL.
Fire Fighting Procedures:WEAR SELF-CONTAINED, POSITIVE PRESSURE
BREATHING APPARATUS AND PROTECTIVE CLOTHES.
Unusual Fire/Explosion Hazard:KEEP AWAY FROM IGNITION SOURCES AND OPEN
FLAMES.

Accidental Release

Spill Release Procedures:OBSERVING HEALTH HAZARDS DESCRIBED ABOVE,
VENTILATE AREA, REMOVE IGNITION SOURCE. CONFINE SPILL, WIPE WITH
RAGS AND TRANSFER TO WASTE DRUM.

Handling

Handling and Storage Precautions:KEEP AWAY FROM IGNITION SOURCES AND
OXIDIZERS. STORE IN A COOL PLACE.
Other Precautions:WEARING CONTACT LENSES IS INADVISABLE!! KEEP AWAY
FROM CHILDREN AND ANIMALS.

Exposure Controls

Respiratory Protection:FOR CONSUMER: N/A. BULK: USE NIOSH APPROVED
SELF- CONTAINED RESPIRATOR.
Ventilation:USE WITH ADEQUATE VENTILATION. GENERAL.
Protective Gloves:SOLVENT RESISTANT GLOVES.
Eye Protection:FULLY PROTECTIVE GOGGLES/FACE SHIELDS.
Other Protective Equipment:SOLVENT RESISTANT APRON.
Supplemental Safety and Health

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:>300F,>149C
Spec Gravity:0.82
Solubility in Water:INSOLUBLE
Appearance and Odor:DARK LIQUID WITH PETROLEUM ODOR.
Percent Volatiles by Volume:90%

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:NORMAL PRODUCTS OF COMBUSTION, SMOKE,
CARBON DIOXIDE, CARBON MONOXIDE AND SULFUR TRIOXIDES.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE



GOVERNMENT LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.