

Material Safety Data Sheet

QUICK IDENTIFIER (In Plant Common Name)

#1818 FIBERED ROOF COATING

Manufacturer's Name
AMERICAN TAR COMPANY

Address
**1700 N. Northlake Way
Seattle, WA 98103**

Emergency Telephone No. (206) 632-0828

Other Information Calls

Signature of Person Responsible for Preparation
[Signature]

Date Prepared Mar. 1986

SECTION 1 - IDENTITY

Common Name: (used on label) (Trade Name & Synonyms) **ATCO #1818 FIBERED ROOF COATING**

Cas No.

Chemical Name **ASPHALT ROOF COATINGS**

Chemical Family **PETROLEUM ASPHALT/PETROLEUM DISTILLATE**

Formula

SECTION 2 - HAZARDOUS INGREDIENTS

Principal Hazardous Component(s) (chemical & common name(s))	%	Threshold Limit Value (units)
MINERAL SPIRITS	28 - 42	500 ppm OSHA 100 ppm ACGIH
ASBESTOS	1 - 8	

Asbestos is a health hazard when inhaled. Once encapsulated, as in this product, it is considered non-hazardous.

SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS (Fire & Explosion Data)

Boiling Point	309°F	Specific Gravity (H ₂ O=1)	.92 - 1.17	Vapor Pressure (mm Hg) < 10 @ 25°C
Percent Volatile by Volume (%)	28 - 42	Vapor Density (Air = 1)	4.8	Evaporation Rate (n-BUTYL ACETATE = 1) Less Than 1
Solubility in Water	Neg.	Reactivity in Water	None	
Appearance and Odor	BLACK VISCOUS WITH ODOR OF PETROLEUM SOLVENT			

Flash Point 105°F
Flammable Limits in Air % by Volume: Lower 0.9, Upper 7.0
Extinguisher Media: FOAM-DRY CHEMICAL
Auto-Ignition Temperature 490°F

Special Fire Fighting Procedures: Heat on closed containers may build up pressure. Do not use water.

Use self-contained breathing apparatus in confined areas.

Unusual Fire and Explosion Hazards: Handle as combustible petroleum products.