

AMERON PROTECTIVE COATINGS DIVISION -- AMERCOAT, 68A CURE, ZINC CHROMATE PRIMER -- 8010-00F006325

=====
Product Identification
=====

Product ID:AMERCOAT, 68A CURE, ZINC CHROMATE PRIMER

MSDS Date:01/01/1987

FSC:8010

NIIN:00F006325

MSDS Number: BBVLK

=== Responsible Party ===

Company Name:AMERON PROTECTIVE COATINGS DIVISION/BREA, CA 92621

Emergency Phone Num:(714) 529-1951

CAGE:0Y2E4

=== Contractor Identification ===

Company Name:AMERON INTERNATIONAL PROTECTIVE COATINGS GROUP

Address:201 NORTH BERRY ST.

Box:City:BREA

State:CA

ZIP:92821

Country:US

Phone:714-529-1951

CAGE:55849

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

Box:1020

City:BREA

State:CA

ZIP:92622-1020

Country:US

Phone:714-529-1951

CAGE:0Y2E4

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHALENE (SARA III)

CAS:91-20-3

RTECS #:QJ0525000

Fraction by Wt: 39%

OSHA PEL:10 PPM/15 STEL

ACGIH TLV:10 PPM/15 STEL; 9192

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:POLYAMIDE RESIN

Fraction by Wt: 32%

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 18%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL N-AMYL KETONE

CAS:110-43-0

RTECS #:MJ5075000

Fraction by Wt: 18%

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9192

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:E01400000

Fraction by Wt: 1%

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

==== Hazards Identification =====

Effects of Overexposure:IRRITATING TO SKIN/MUCOUS
MEMBRANES/EYES/RESPIRATORY SYSTEM/HEADACHE/NAUSEA/KIDNEY & LIVER
DAMAGE.

==== First Aid Measures =====

First Aid:INHALATION: PROVIDE FRESH AIR. SKIN: RINSE W/5% ACETIC ACID,
THEN WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/WATER FOR AT
LEAST 15 MINS/GET MED ATT. LAUNDRER CONTAMINATED CLOTHING BEFORE
REUSE. INGESTION: DON'T INDUCE VOMITING. CALL PHYSICIAN.

==== Fire Fighting Measures =====

Flash Point:95F (SETA)

Lower Limits:0.9%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT,
SPARKS AND OPEN FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. USE
ABSORBENT CLEANUP MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. STORE IN COOL,
WELL VENTILATED AREA. IN CONFINED AREAS/TANKS/STAGNANT A
CONDITIONS, USE EXPLOSION/SPARK-PROOF EQUIPMENT.

Other Precautions:AVOID PROLONGED BREATHING OF VAPORS OR SPRAY MIST OR
CONTACT WITH SKIN & EYES. DESTROY ALL LEATHER MATERIAL WHICH
CANNOT
BE CONTAMINATED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATOR. IN CONFINED AREAS,
USE AIRLINE HOOD RESP.

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:69%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS, EPOXY RESIN UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid:HEAT, OPEN FLAME, ARC OR SPARKS.

Hazardous Decomposition Products:CO, CO2 & NOX

===== Disposal Considerations =====

Waste Disposal Methods:IN SEPARATE CLOSED METAL CONTAINER IN
ACCORDANCE

WITH ALL APPLICABLE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.