

MATERIAL SAFETY DATA SHEET

B69R60
05 00

DATE OF PREPARATION
Dec 6, 2011

SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER

B69R60

PRODUCT NAME

TAR GUARD™ Coal Tar Epoxy (Part A), Red

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY
101 Prospect Avenue N.W.
Cleveland, OH 44115

Telephone Numbers and Websites

| | |
|----------------------------------|-------------------------------------|
| Product Information | www.sherwin-williams.com |
| Regulatory Information | (216) 566-2902 www.paintdocs.com |
| Medical Emergency | (216) 566-2917 |
| Transportation Emergency* | (800) 424-9300 |

**for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)*

SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

| % by Weight | CAS Number | Ingredient | Units | Vapor Pressure | |
|-------------|-------------|---------------------------------------|--|--|--------|
| 1 | Proprietary | Polycyclic Aromatic Compounds | ACGIH TLV OSHA PEL | Not Available Not Available | |
| 3 | 100-41-4 | Ethylbenzene | ACGIH TLV ACGIH TLV OSHA PEL OSHA PEL | 100 PPM 125 PPM STEL 100 PPM 125 PPM STEL | 7.1 mm |
| 18 | 1330-20-7 | Xylene | ACGIH TLV ACGIH TLV OSHA PEL OSHA PEL | 100 PPM 150 PPM STEL 100 PPM 150 PPM STEL | 5.9 mm |
| 1 | 90-72-2 | Tri(dimethylaminomethyl)phenol | ACGIH TLV OSHA PEL | Not Available Not Available | |
| 33 | 65996-93-2 | Refined Coal Tar Pitch | ACGIH TLV OSHA PEL | 0.2 MG/M3 0.2 MG/M3 | |
| 11 | 68410-23-1 | Polyamide | ACGIH TLV OSHA PEL | Not Available Not Available | |
| 10 | 14807-96-6 | Talc | ACGIH TLV OSHA PEL | 2 mg/m3 as Resp. Dust 2 mg/m3 as Resp. Dust | |

SECTION 3 — HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.
EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Causes burns.

SKIN: Causes burns.

INHALATION: Causes burns of the upper respiratory system.

HMIS Codes

| | |
|---------------------|----|
| Health | 3* |
| Flammability | 3 |
| Reactivity | 0 |

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the liver
- the urinary system
- the reproductive system

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

May cause allergic skin reaction in susceptible persons or skin sensitization.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

SECTION 4 — FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention **IMMEDIATELY**.

SKIN: Wash affected area thoroughly with soap and water.
If irritation persists or occurs later, get medical attention.
Discard contaminated clothing and shoes.

INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

INGESTION: Do not induce vomiting. Get medical attention immediately.

SECTION 5 — FIRE FIGHTING MEASURES

| | | | |
|--------------------|------------|------------|--|
| FLASH POINT | LEL | UEL | FLAMMABILITY CLASSIFICATION |
| 90 °F PMCC | 1.0 | 7.0 | RED LABEL -- Flammable, Flash below 100 °F (38 °C) |

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

SECTION 7 — HANDLING AND STORAGE

STORAGE CATEGORY

DOL Storage Class IC

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Contents are **FLAMMABLE**. Keep away from heat, sparks, and open flame.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Do not get in eyes, or on skin or clothing. Do not breathe vapor or spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits.

Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

For spray application, wear a full face positive pressure air supplied respirator, TC19C NIOSH/MSHA approved. For brush application, wear an organic vapor NIOSH/MSHA approved respirator. Follow respirator manufacturer's directions for use.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear Nitrile/NBR gloves.

EYE PROTECTION

To prevent eye contact, wear safety spectacles with unperforated sideshields.

OTHER PROTECTIVE EQUIPMENT

Use barrier cream on exposed skin. For spray application, wear full body disposable protective clothing.

OTHER PRECAUTIONS

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

| |
|---|
| SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES |
|---|

| | | |
|---|---------------------|--|
| PRODUCT WEIGHT | 11.50 lb/gal | 1378 g/l |
| SPECIFIC GRAVITY | 1.38 | |
| BOILING POINT | 277 - 292 °F | 136 - 144 °C |
| MELTING POINT | Not Available | |
| VOLATILE VOLUME | 33% | |
| EVAPORATION RATE | Slower than ether | |
| VAPOR DENSITY | Heavier than air | |
| SOLUBILITY IN WATER | N.A. | |
| VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged) | | |
| | 2.40 lb/gal 288 g/l | Less Water and Federally Exempt Solvents |
| | 2.40 lb/gal 288 g/l | Emitted VOC |

| |
|--|
| SECTION 10 — STABILITY AND REACTIVITY |
|--|

STABILITY — Stable**CONDITIONS TO AVOID**

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

| |
|---|
| SECTION 11 — TOXICOLOGICAL INFORMATION |
|---|

CHRONIC HEALTH HAZARDS

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Ethylbenzene is classified by IARC as possibly carcinogenic to humans (2B) based on inadequate evidence in humans and sufficient evidence in laboratory animals. Lifetime inhalation exposure of rats and mice to high ethylbenzene concentrations resulted in increases in certain types of cancer, including kidney tumors in rats and lung and liver tumors in mice. These effects were not observed in animals exposed to lower concentrations. There is no evidence that ethylbenzene causes cancer in humans.

Coal Tar Pitch is listed by NTP. Human and animal studies indicate that prolonged overexposure to Coal Tar Pitch can cause cancer of the skin, lung, bladder and gastrointestinal tract. Inhalation of Coal Tar Pitch Volatiles at application temperatures would not be expected as they are vaporized only at very high temperatures.

TOXICOLOGY DATA

| CAS No. | Ingredient Name | | | |
|-------------|--------------------------------|----------|-----|---------------|
| Proprietary | Polycyclic Aromatic Compounds | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | Not Available |
| 100-41-4 | Ethylbenzene | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | 3500 mg/kg |
| 1330-20-7 | Xylene | LC50 RAT | 4HR | 5000 ppm |
| | | LD50 RAT | | 4300 mg/kg |
| 90-72-2 | Tri(dimethylaminomethyl)phenol | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | 1653 mg/kg |
| 65996-93-2 | Refined Coal Tar Pitch | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | Not Available |
| 68410-23-1 | Polyamide | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | Not Available |
| 14807-96-6 | Talc | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | Not Available |

SECTION 12 — ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

SECTION 13 — DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

SECTION 14 — TRANSPORT INFORMATION

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

US Ground (DOT)

5 Liters (1.3 Gallons) and Less may be Classed as CONSUMER COMMODITY, ORM-D
 Larger Containers are Regulated as:
 UN1263, PAINT, 3, PG III, (ERG#128)

DOT (Dept of Transportation) Hazardous Substances & Reportable Quantities

Ethyl benzene 1000 lb RQ
 Xylenes (isomers and mixture) 100 lb RQ

Bulk Containers may be Shipped as (check reportable quantities):

RQ, UN1263, PAINT, 3, PG III, (XYLENES (ISOMERS AND MIXTURE)), (ERG#128)

Canada (TDG)

UN1263, PAINT, CLASS 3, PG III, LIMITED QUANTITY, (ERG#128)

IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.
 UN1263, PAINT, CLASS 3, PG III, (32 C c.c.), EmS F-E, S-E, ADR (D/E)

IATA/ICAO

UN1263, PAINT, 3, PG III

SECTION 15 — REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

| CAS No. | CHEMICAL/COMPOUND | % by WT | % Element |
|-------------|-------------------------------|---------|-----------|
| Proprietary | Polycyclic Aromatic Compounds | 1 | |
| 100-41-4 | Ethylbenzene | 3 | |
| 1330-20-7 | Xylene | 18 | |

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.