



SAFETY DATA SHEET

PSX 700 CURE

1. Identification of the substance/preparation and of the company/undertaking

Product Name : PSX 700 CURE
MSDS No. : M-10700CA
Area of Application : **FOR INDUSTRIAL USE ONLY**
Product Use : Engineered siloxane coating (Cure component)
US Patent nos. 5,618,860 and 5,275,645
Supplier/Manufacturer : Performance Coatings & Finishes Europe
Ameron BV
J.F.Kennedylaan 7
P.O. Box 6, 4190 CA, Geldermalsen, The Netherlands
Telephone No. : +31 345 587587
Fax: : +31 345 587551
Emergency phone : +31 345 587587

2. Composition/information on ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name*	CAS no.	%	Classification
3-Aminopropyltriethoxysilane	919-30-2	60-100	Xn; R22 C; R34
Organosilane ester		10-30	Xi; R36/38
Organotin		5-10	Xn; R22

See Section 16 for the full text of the R Phrases declared above

* Occupational Exposure Limit(s), if available, are listed in Section 8

3. Hazards identification

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Physical/chemical Hazards : Not applicable.
Human health hazards : Harmful if swallowed.
Causes burns.
Environmental hazards : Not applicable.

4. First-aid measures

First-Aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.
Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Eye Contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

PSX 700 CURE

5. Fire-fighting measures

- Extinguishing Media** : Recommended: alcohol resistant foam, CO2, powders, water spray.
Not to be used : waterjet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

6. Accidental release measures

- Personal Precautions** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

Note: See section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

- Handling** : Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.
- Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates and spray mist arising from the application of this preparation. Avoid inhalation of dust from sanding.
- Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Put on appropriate personal protective equipment (see Section 8).
- Never use pressure to empty : container is not a pressure vessel. Always keep in containers of same material as the original one.
- Comply with the health and safety at work laws.
- When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.
- Storage** : Store in accordance with local regulations. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources.
- Keep away from: OXIDIZING AGENTS, strong alkalis, strong acids.
No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Do not empty into drains..

8. Exposure controls/personal protection

- Engineering measures** : Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Ingredient Name

3-Aminopropyltriethoxysilane
Organosilane ester
Organotin

Occupational Exposure Limits

Not available.
Not available.
Not available.

Personal protective equipment

- Respiratory system** : If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.
- Skin and body** : Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

PSX 700 CURE

- Hands** : For prolonged or repeated handling, use gloves: nitrile.
Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.
- Eyes** : Use safety eyewear designed to protect against splash of liquids.

Environmental exposure control

Do not allow to enter drains or watercourses.

9. Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : Closed cup: 96°C (204.8°F). (Setaflash.)
- Specific gravity** : 0.981 g/cm³ (25°C / 77°F)
- Vapour density** : >1 (Air = 1)
- Explosion Limits** : LOWER: 3.5% UPPER: 19%
- Solubility** : Insoluble in cold water, hot water.

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous Decomposition Products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials in order to avoid strong exothermic reactions: OXIDIZING AGENTS, strong alkalis, strong acids.

11. Toxicological information

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 15 for details. See Chapters 2 and 15 for details.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

12. Ecological information

There are no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

13. Disposal considerations

Do not allow to enter drains or watercourses.
Dispose of according to all federal, state and local applicable regulations.

14. Transport information

Land - Road/Railway

- UN number** : 1760
- Transport document name** : Corrosive liquid, N.O.S. (Siloxane compound)
- ADR/RID Class** : 8
- Packing group** : III
- ADR/RID label** :



- Hazard identification number** : 80

Sea

- UN number** : 1760

PSX 700 CURE

Proper shipping name : Corrosive liquid, N.O.S. (Siloxane compound)
IMDG Class : 8
Packing group : III
IMDG label :



Marine pollutant : No.
Emergency Schedules (EmS) : 8-15

Air

UN number : 1760
Proper shipping name : Corrosive liquid, N.O.S. (Siloxane compound)
ICAO/IATA Classification : 8
Packing group : III
ICAO/IATA label :



15. Regulatory information

EU Regulations : The product is labelled as follows, in accordance with local regulations:

Hazard symbol(s) :



Corrosive

Indication of Danger : Corrosive
Risk Phrases :

R22- Harmful if swallowed.
R34- Causes burns.

Safety Phrases :

S23 - Do not breathe gas/fumes/vapour/spray.
S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39 - Wear suitable protective clothing, gloves and eye/face protection.
S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S51 - Use only in well-ventilated areas.

Contains :

3-Aminopropyltriethoxysilane

16. Other information

Full text of R-Phrases with no. appearing in Section 2 - United Kingdom (UK) : R22- Harmful if swallowed.
R34- Causes burns.
R36/38- Irritating to eyes and skin.

Date of printing : 8/21/2002.
Date of issue : 8/5/2002.
Version : 1

Notice to Reader

The information of this SDS is based on the present state of our knowledge and on current EU and national laws. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product : it is not to be considered as a guarantee of the products properties.

MSDS No. : M-10700CA

Page: 4/4