
1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Polyken 1027 Primer
Product Description Pipe Corrosion Protection
Manufacturer/Supplier Berry Plastics Corporation, Tapes and Coatings Division
Address 2320 Bowling Green Road
Franklin, Kentucky
Phone Number (270) 586-3261 (Monday – Friday 8:00 am to 5:00 pm)
Chemtrec Number (800) 424-9300
Revision Date: May 16, 2008
MSDS Date: November 15, 2007

This MSDS has been compiled in accordance with - EC Directive 91/155/EC - OSHA's Hazcom Standard (29 CFR 1910.1200)

2. HAZARDS IDENTIFICATION

EU Main Hazards

R11 Highly flammable.
R36/38 Irritating to eyes and skin.
R45 May cause cancer.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63 Possible risk of harm to the unborn child.
R65 Harmful: may cause lung damage if swallowed.
R67 Vapours may cause drowsiness and dizziness.

Routes of Entry

- Absorption - Eye contact - Ingestion - Inhalation - Skin contact

Carcinogenic Status

See Section 11.

Target Organs

Central Nervous System - Skin - Eye - Liver - Kidney - Respiratory System - Reproductive

Health Effects - Eyes

Liquid, mist or vapor may cause pain, transient irritation and superficial corneal effects.

Health Effects - Skin

Material may cause irritation. Repeated or prolonged contact may produce defatting of the skin leading to irritation and dermatitis. Material can be absorbed through the skin and cause effects similar to those resulting from inhalation.

Health Effects - Ingestion

Swallowing may have the following effects:

- abdominal pain - vomiting - central nervous system depression - kidney damage - liver damage – testis damage – aspiration into the lungs may occur during ingestion or vomiting causing lung damage

A large dose may have the following effects:

- systemic effects similar to those resulting from inhalation

2. HAZARDS IDENTIFICATION

Health Effects - Inhalation

Exposure to vapor may have the following effects:

- irritation of nose, throat and respiratory tract - central nervous system depression - dizziness - drowsiness - headache - mental confusion

Exposure to vapor at high concentrations may have the following effects:

- nerve damage leading to numbness and muscle weakness - lung damage - liver damage - kidney damage - testis damage – adverse reproductive effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS#/Codes	Concentration	R Phrases	Classification
Aliphatic Petroleum Distillate	64742-89-8 265-192-2	60 - 80%	R45, R65	T, Xn, Carc Cat. 2
Toluene	108-88-3 203-625-9	5 - 10%	R11, R38, R48/20, F, Xn R63, R65, R67	
Carbon Black	1333-86-4 215-609-9	<5%	None	None
Polymers and Resins	N.A.	<25%	None	None

4. FIRST AID MEASURES

Eyes

Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

Skin

Immediately flood the skin with large quantities of water for at least 15 minutes, preferably under a shower. Remove contaminated clothing and continue washing. Contaminated clothing should be washed or dry-cleaned before re-use. Obtain medical attention if blistering occurs or redness persists.

Ingestion

Do not induce vomiting, unless directed to do so by a physician. Have victim drink 1-3 glasses of water to dilute stomach contents. If there is difficulty in breathing, give oxygen. Obtain medical attention immediately.

Inhalation

Remove from exposure. If there is difficulty in breathing, give oxygen. Obtain medical attention immediately.

Advice to Physicians

Treat symptomatically.

5. FIRE- FIGHTING MEASURES

Extinguishing Media

Use foam, dry chemical or carbon dioxide. Be aware of the possibility of re-ignition. Keep containers and surroundings cool with water spray.

Unusual Fire and Explosion Hazards

Vapors can travel a considerable distance to a source of ignition and flashback. Flashback can occur if air temperature exceeds flash point. Be aware of possibility of re-ignition.

Protective Equipment for Fire-Fighting

Wear full protective clothing and self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal. Wear appropriate protective clothing. Eliminate all sources of ignition. Use non-sparking scoops for flammable materials. Vapors can accumulate in low areas. Consider need for evacuation. Prevent the material from entering drains or watercourses. Notify authorities if spill has entered watercourse or sewer or has contaminated soil or vegetation.

7. HANDLING AND STORAGE

Use in well ventilated area. Use local exhaust ventilation. Avoid inhaling vapor. Avoid contact with eyes, skin and clothing. Keep container tightly closed when not in use.

Store away from sources of heat or ignition. Storage area should be: - cool - dry - well ventilated - out of direct sunlight – away from sources of ignition(heat, sparks, flames, pilot lights) - away from incompatible materials (see Section 10)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards

Exposure limits are listed below, if they exist.

Toluene

ACGIH: TLV 20ppm (75 mg/m³) 8h TWA

OSHA: PEL 200ppm 8h TWA. 300 ppm CEILING, 500 ppm 10-min peak per shift.

Aliphatic Petroleum Distillate

ACGIH: TLV 300ppm (1370 mg/m³) 8h TWA (as VM&P naphtha 8032-32-4)

OSHA: PEL 500ppm (2000 mg/m³) 8h TWA. (as Petroleum distillates)

Carbon Black

ACGIH: TLV 3.5 mg/m³ 8h TWA

OSHA: PEL 3.5 mg/m³ 8h TWA

Polymers and Resins

None assigned.

Engineering Control Measures

Use engineering methods to prevent or control exposure. Methods include process or personnel enclosure, mechanical ventilation (dilution and local exhaust), and control of process conditions.

Respiratory Protection

Wear respiratory protection if there is a risk of exposure to high vapor concentrations, aerosols or if applied to hot surfaces. A NIOSH approved full face respirator may be worn. The specific respirator selected must be based on the airborne concentration found in the workplace and must not exceed the working limits of the respirator.

Hand Protection

Butyl gloves are recommended.

Eye Protection

Chemical goggles or safety glasses with side shields. Consider the use of a face shield if splashing is possible.

Body Protection

If there is danger of splashing, wear: - overall or apron

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Color	Black
Odor	Light Hydrocarbon
pH	No data

9. PHYSICAL AND CHEMICAL PROPERTIES

Density (lbs/gal)	No data
Boiling Range/Point (°C/F)	No data
Melting Point (°C/F)	Not applicable
Flash Point (°F)	Est. 40 – 50 °F
Vapor Pressure	No data
Evaporation Rate	Slower than ether
Solubility in Water	Negligible
Vapor Density	Heavier than air.
VOC	78.9%

10. STABILITY AND REACTIVITY

Stability

Stable under normal conditions.

Conditions to Avoid

- Heat, sparks, flames - High temperatures - sources of ignition - contact with incompatible materials

Materials to Avoid

- Strong oxidizing agents - acids - bases - reducing agents - halogens - hydrogen

Hazardous Polymerization

Will not occur.

Hazardous Decomposition Products

- oxides of carbon - hydrocarbons – phenolic vapors – aldehydes -smoke -fumes

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Toluene: Oral LD50 rat >2,000 mg/kg. Dermal LD50 rabbit >3,000 mg/kg

Chronic Toxicity/Carcinogenicity

Aliphatic Petroleum Distillate (as VM&P naphtha 8032-32-4): ACGIH Carcinogen Category: A3
(Confirmed Animal Carcinogen with Unknown Relevance to Humans)

This product contains carbon black which is classified by IARC as a Group 2B possible human carcinogen. When encapsulated in the liquid matrix the risk of exposure is reduced.

Genotoxicity

This product is not expected to cause any mutagenic effects.

Reproductive/Developmental Toxicity

Toluene: In laboratory studies, birth defects, increased fetal lethality and delayed fetal development have been observed in offspring of female animals exposed during pregnancy. Toluene has been demonstrated to be embryofetotoxic and teratogenic in laboratory animals.

12. ECOLOGICAL INFORMATION

Mobility

No relevant studies identified.

Persistence/Degradability

No relevant studies identified.

Bio-accumulation

No relevant studies identified.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toluene: LC50 Fathead minnow (Pimephales promelas) 96 h 26 ppm. EC50 Daphnia magna 48 h 11.5 ppm

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld on or near to the container. Use non-sparking tools. Do not incinerate closed containers. Empty containers may contain hazardous residues. Dispose of containers with care.

14. TRANSPORT INFORMATION

DOT CFR 172.101 Data	Coating Solution (3) UN1139, II
UN Proper Shipping Name	Coating Solution
UN Class	(3)
UN Number	UN1139
UN Packaging Group	II
Classification for AIR Transportation (IATA)	Consult current IATA Regulations prior to shipping by air.

15. REGULATORY INFORMATION

EU Label Information

Classification and labelling have been performed according to EU directives 67/548/EEC and 99/45/EC including amendments(2001/60/EC and 2006/8/EC)

EU Hazard Symbol and Indication of Danger

T- Toxic

F- Flammable

R phrases

R11 Highly flammable.

R36/38 Irritating to eyes and skin.

R45 May cause cancer.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63 Possible risk of harm to the unborn child.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

S phrases

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37 Wear suitable protective clothing and gloves.

S45 In case of accident or if you feel unwell, seek medical advice immediately.

S53 Avoid exposure – obtain special instructions before use.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

US REGULATIONS (Federal, State) and INTERNATIONAL CHEMICAL REGISTRATION LAWS**TSCA Listing**

All ingredients have been verified for inclusion on the EPA Toxic Substance Control Act Chemical Substance Inventory.

15. REGULATORY INFORMATION

EINECS Listing

All ingredients in this product have not been verified for inclusion on the European Inventory of Existing Commercial Chemical Substances (EINECS).

DSL (Canadian) Listing

All ingredients in this product have not been verified for inclusion on the Domestic Substance List (DSL).

MA Right To Know Law

This product contains the following chemicals found on the Massachusetts Substance List (MSL).
Toluene (108-88-3) 5 -10 %– Methanol (67-56-1) <1% - Xylene (1330-20-7) <1%

PA Right To Know Law

This product contains the following chemicals found on the Pennsylvania Hazardous Substance List:
Carbon black (1333-86-4) < 5% - Toluene (108-88-3) 5 -10 % – Methanol (67-56-1) <1% - Xylene (1330-20-7) <1% - Ethylbenzene (100-41-4) <0.1%

NJ Right To Know Law

This product contains the following chemicals found on the NJ Right To Know Hazardous Substance List: Toluene (108-88-3) 5 -10 % – Methanol (67-56-1) <1% - Xylene (1330-20-7) <1% - Carbon black (1333-86-4) < 5%

California Proposition 65

This product contains the following materials which the State of California has found to cause cancer, birth defects or other reproductive harm: Toluene (108-88-3) - Ethylbenzene (100-41-4) - Formaldehyde (50-00-0) trace – Benzene (71-43-2)

WHMIS Classification

B2.D2A

This product was classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations and the MSDS contains all the information required by these regulations.

SARA Title III Sect. 311/312 Categorization

Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard, Fire Hazard

SARA Title III Sect. 313

This product contains a chemical that is listed in Section 313 at or above de minimis concentrations. The following listed chemicals are present: Toluene (108-88-3)

16. OTHER INFORMATION

NFPA Ratings

NFPA Code for Flammability - 4
NFPA Code for Health - 2
NFPA Code for Reactivity - 0
NFPA Code for Special Hazards – None

HMIS Ratings

HMIS Code for Flammability - 4
HMIS Code for Health - 2
HMIS Code for Reactivity - 0
HMIS Code for Personal Protection - See Section 8

Abbreviations

N/A: Denotes no applicable information found or available
CAS#: Chemical Abstracts Service Number
ACGIH: American Conference of Governmental Industrial Hygienists
OSHA: Occupational Safety and Health Administration
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
STEL: Short Term Exposure Limit

16. OTHER INFORMATION

NTP: National Toxicology Program
IARC: International Agency for Research on Cancer
R: Risk
S: Safety

For further information email: msdstechnical@berryplastics.com

Prepared By: EnviroNet LLC.

The information and recommendations presented in this MSDS are based on sources believed to be accurate. Berry Plastics Corporation, Tapes and Coatings Division assumes no liability for the accuracy or completeness of this information. It is the user's responsibility to determine the suitability of the **material** for their particular purposes. In particular, we make **NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED**, with respect to such information, and we assume no liability resulting from its use. Users should ensure that any use **or disposal** of the material is in accordance with applicable Federal, State, and local laws and regulations.
