



350 Hanley Industrial Ct. • St. Louis, MO 63144-1599  
 an **rpm** company • 314-644-1000

CARBOLINE CO. MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT: SUPER HI-GARD 894 LT PART A (0980A1NL)  
 Date: 12/29/95 Replaces 11/30/94

CHEMTREC TRANSPORTATION EMERGENCY PHONE NO.: 800-424-9300  
 PITTSBURGH POISON CONTROL CENTER HEALTH EMERGENCY NO.: 412-681-6669

SECTION II - HAZARDOUS INGREDIENTS EXPOSURE LIMITS

CHEMICAL NAME	(A)	(B)	(C)	(D)	(E)
COLOR PIGMENT	MIXTURE	25%	3.5MG/M3	NE	NE
SILICA	14808-60-7	20%	0.1MG/M3	NE	NE
XYLENE	1330-20-7	5%	100 PPM	150 PPM	NE
METHYL ETHYL KETONE	78-93-3	5%	200 PPM	300 PPM	NE
MIBK	108-10-1	5%	50 PPM	75 PPM	NE

CHEMICAL NAME	HAZARDOUS INGREDIENTS (F)	ADDITIONAL DATA	(G)
COLOR PIGMENT	NOT AVAILABLE		NO/NO
SILICA	NOT AVAILABLE		NO/NO/NR/NO
XYLENE	4300MG/KG RAT, ORAL 15000 PPM/4HRS RAT, INHALATION		NO/YES/1,2,3/ 1000#/U239
METHYL ETHYL KETONE	2737MG/KG RAT, ORAL 2000PPM/H HRS RAT, INHALATION		NO/YES/1,2,3/ 5000
MIBK	NOT AVAILABLE		NO/YES/1,2,3/ 5000#/U161

TABLE (A) CAS NUMBER (B) LESS THAN WT (C) TLV-TWA (D) STEL (E) CEILING (F) TOXICITY DATA (LD50/Route, LC50/Route) (G) SARA 302/SARA 313/ SARA 311-312 CATEGORIES/CERCLA. NE = not established, NR = not required, NO = no. Color Pigment Mixture may contain Iron Oxides, Titanium Dioxide, Carbon Black, and other particulates not otherwise regulated in varying amounts depending on color of product.

WHMIS CLASSIFICATION: B2 -- D2A -- D2B  
 HMIS/NFPA CLASSIFICATION: HEALTH 3, FLAMMABILITY 3, REACTIVITY 0,  
 PERSONAL PROTECTION CODE G, NFPA FIRE FIGHTING PHASE 4

SECTION III - PHYSICAL DATA:

BOILING RANGE: 175F(79C)-284F(140C). VAPOR DENSITY: Heavier than air.  
 EVAPORATION RATE: Slower than ether. VOLATILE BY WEIGHT 8 %. VOLATILE BY VOLUME: 14 %. PRODUCT WT/GAL: 12.1 LBS/U.S.GAL. 1.45 sp gr. VOC (MIXED PRODUCT THINNED TO MAXIMUM LEVEL): 2.5 LBS/U.S.GAL. 298 gm/lr.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

FLAMMABILITY CLASSIFICATION: FLASH POINT: 25 F(-3C) (Setaflash) LEL 1.0 % UEL 10.1 %.  
 OSHA-PAINT/FLAMMABLE/LIQUID/3/UN1263/PGII, DOT-PAINT,3,UN1263,PGII, CANADIAN TDGA: PAINT,3,UN1263,PGII  
 EXTINGUISHING MEDIA: Dry Chemical, Foam, Carbon Dioxide, Water Fog.  
 UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and will



350 Hanley Industrial Ct. • St. Louis, MO 63144-1599  
an **rpm** company • 314-644-1000

CARBOLINE CO. MATERIAL SAFETY DATA SHEET

PAGE 2 of 3

PRODUCT: SUPER HI-GARD 894 LT PART A (0980A1NL)

Date: 12/29/95 Replaces 11/30/94

accumulate. Vapors will form explosive concentrations with air. Vapors travel long distances and will flashback. Use mechanical ventilation when necessary to keep percent vapor below the "Lower Explosion Level" (LEL).  
SPECIAL FIRE FIGHTING PROCEDURES: Evacuate hazard area of unprotected personnel. Use a NIOSH approved self-contained breathing unit and complete body protection. Cool surrounding containers with water in case of fire exposure.

SECTION V - HEALTH HAZARD DATA:

-----  
INHALATION: Harmful if inhaled, may affect the brain or nervous system, causing dizziness, headache or nausea. May cause nose and throat irritation.  
CONTACT: May cause eye irritation. May cause skin irritation.  
NOTICE: Contains SILICA which can cause cancer. Risk of cancer depends on duration and level of exposure. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.  
MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: If you have a condition that could be aggravated by exposure to dust or organic vapors see a physician prior to use.  
PRIMARY ROUTE(S) OF ENTRY: Inhalation, Dermal, Ingestion.  
EMERGENCY FIRST AID PROCEDURES: When exposed always get medical attention.  
EYE CONTACT: Flush with water for 15 minutes.  
SKIN CONTACT: Wash with soap and water. Remove contaminated clothing and clean before reuse.  
INHALATION: Remove to fresh air. Provide oxygen if breathing is difficult. Use artificial respiration if not breathing. Get medical attention.  
IF SWALLOWED: DO NOT INDUCE VOMITING!! Always get medical attention.

SECTION VI - REACTIVITY DATA:

-----  
STABILITY: This product is stable under normal storage conditions.  
HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.  
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, nitrogen oxides, and unidentified organic compounds. Consider all smoke and fumes from burning material as very hazardous. Welding, cutting or abrasive grinding can create smoke and fumes. Do not breathe.  
CONDITIONS TO AVOID: Heat, sparks, and open flames.  
INCOMPATIBILITY: Avoid contact with strong oxidizing agents.

SECTION VII - SPILL OR LEAK PROCEDURES:

-----  
STEPS TO BE TAKEN IN CASE OF SPILL: Eliminate all ignition sources. Handling equipment must be grounded to prevent sparking. Evacuate the area of unprotected personnel. Wear appropriate personal protection clothing and equipment. Follow safe handling and use guidelines in Section VIII. Contain and soak up residual with an absorbent (clay or sand). Take up absorbent material and seal tightly for proper disposal. Dispose of in accordance with local, state and federal regulations. Refer to Section II for Sara Title III



350 Hanley Industrial Ct. • St. Louis, MO 63144-1599  
an **FDI** company • 314-644-1000

CARBOLINE CO. MATERIAL SAFETY DATA SHEET

PAGE 3 of 3

PRODUCT: SUPER HI-GARD 894 LT PART A (0980A1NL)  
Date: 12/29/95 Replaces 11/30/94

and CERCLA information.

SECTION VIII - SAFE HANDLING AND USE INFORMATION:

RESPIRATORY PROTECTION: Use only with ventilation to keep levels below exposure guidelines. (Section II). User should test and monitor exposure levels to insure all personnel are below guidelines. If not sure or if not able to monitor use MSHA/NIOSH approved air-purifying respirator.

VENTILATION: Use explosion-proof ventilation when required to keep below health exposure guidelines and Lower Explosion Limit (LEL).

SKIN AND EYE PROTECTION: Recommend impervious gloves, clothing and safety glasses with side shields or chemical goggles to avoid skin and eye contact. If material penetrates to skin, change gloves and clothing.

HYGIENIC PRACTICES: Wash with soap and water before eating, drinking, applying cosmetics, or using toilet facilities. Use of a hand cleaner is recommended. Launder contaminated clothing before reuse. Leather shoes can absorb and pass through hazardous materials. Check shoes carefully after soaking before reuse.

SECTION IX - SPECIAL PRECAUTIONS:

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep away from heat, sparks, open flame, and strong oxidizing agents. Keep containers closed. Store in cool, dry place with adequate ventilation. If pouring or transferring materials, ground all containers and tools.

OTHER PRECAUTIONS: Do not weld, heat, cut or drill on full or empty containers.

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Carboline Company 350 Hanley Ind. Ct. St. Louis, MO 63144  
PHONE NO. 314-644-1000 FOR INDUSTRIAL USE ONLY