



Material Safety Data Sheet

**CHEMTREC Transportation
Emergency Phone: 800-424-
9300**

**Pittsburgh Poison Control
Center
Health Emergency No.: 412-
681-6669**

•NOTE: The CHEMTREC Transportation
•Emergency Phone is to be used only in the
•event of chemical emergencies involving a
•spill, leak, fire, exposure or accident
•involving chemicals

Section 1 - Chemical Product / Company Information

Product Name: URETHANE CONVERTER 133 **Revision Date:** 03/28/2011
Identification Number: PLMSDS 0840B1NL **Supercedes :** 09/09/2010
Product Use/Class: Catalyst for Polyurethane Products -
FOR INDUSTRIAL USE ONLY **Preparer:** Regulatory, Department
Manufacturer: Carboline Company
2150 Schuetz Road
St. Louis, MO 63146
(800) 848-4645

Section 2 - Composition / Information On Ingredients

Chemical Name	CAS Number	Weight % Less Than	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA-CEIL
HOMOPOLYMER OF HDI	28182-81-2	75.0	N/E	N/E	N/E	N/E
N-BUTYL ACETATE	123-86-4	15.0	150 PPM	200 PPM	710 MG/M3	N/E
META-XYLENE	108-38-3	10.0	434 Mg/M3	651 Mg/M3	434 Mg/M3	N/E
PARA-XYLENE	106-42-3	5.0	100 PPM	150 PPM	435 MGM3	N/E
ETHYL BENZENE	100-41-4	5.0	100 PPM	125 PPM	435 MGM3	N/E
ORTHO-XYLENE	95-47-6	5.0	434 Mg/M3	651 Mg/M3	434 Mg/M3	N/E
HEXAMETHYLENE DIISOCYANATE	822-06-0	0.6	0.005 PPM	N/E	N/E	N/E

Section 3 - Hazards Identification

Emergency Overview: Reacts violently with common materials including water, alcohols, bases and amines. Harmful if inhaled. Eye, skin and respiratory tract irritant. Possible sensitizer.

Effects Of Overexposure - Eye Contact: May cause eye irritation.

Effects Of Overexposure - Skin Contact: Irritant. May produce symptoms similar to those from inhalation. Can cause dryness, loss of natural oils, allergic reaction.

Effects Of Overexposure - Inhalation: Harmful if inhaled. May cause hoarseness, upper respiratory tract irritation, intoxication, headache, confusion, coma, liver damage, kidney damage.

Effects Of Overexposure - Ingestion: Harmful if ingested. May produce symptoms similar to those from inhalation. Can cause nausea, abdominal cramps.

Effects Of Overexposure - Chronic Hazards: Prolonged contact may cause liver damage, kidney damage, chronic damage to intestines, central nervous system damage, dizziness, weakness, headache, nausea. Repeated, prolonged contact may cause intestinal disturbances. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Ingestion, Eye Contact

Medical Conditions Prone to Aggravation by Exposure: If sensitized to isocyanates or other chemicals, do not use. See a physician if a medical condition exists.

Section 4 - First Aid Measures

First Aid - Eye Contact: If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

First Aid - Skin Contact: In case of contact, immediately wash with plenty of soap and water for at least 15 minutes. Seek medical attention. Remove contaminated clothing and shoes. Clean contaminated clothing and shoes before re-use.

First Aid - Inhalation: If inhaled, remove to fresh air. Administer oxygen if necessary. Consult a physician if symptoms persist or exposure was severe.

First Aid - Ingestion: If swallowed do not induce vomiting. Seek immediate medical attention.

Section 5 - Fire Fighting Measures

Flash Point, F: 91F (32C)
(Setaflash)

Lower Explosive Limit, %: 1.0
Upper Explosive Limit, %: 10.4

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam

Unusual Fire And Explosion Hazards: No Information.

Special Firefighting Procedures: Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing. Cool tightly closed containers exposed to fire with water.

Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: No Information.

Section 7 - Handling And Storage

Handling: Do not get in eyes, on skin, or on clothing. Keep container tightly closed when not in use. Wear personal protection equipment. Do not breathe vapors. Wash thoroughly after handling. If pouring or transferring materials, ground all containers and tools. Do not weld, heat, cut or drill on full or empty containers. Use only in accordance with Carboline application instructions, container label and Product Data Sheet.

Storage: No Information.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls: Use explosion-proof ventilation when required to keep below health exposure guidelines and Lower Explosion Limit (LEL).

Respiratory Protection: Use only with ventilation to keep levels below exposure guidelines listed in Section 2. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not in a confined space, and not able to monitor, use MSHA/NIOSH approved organic vapor respirator. Follow all current OSHA requirements for respirator use.

Skin Protection: Recommend impervious gloves and clothing to avoid skin contact. If material penetrates to skin, change gloves and clothing. The use of protective creams may be beneficial to certain individuals. Protective creams should be applied before exposure.

Eye Protection: Recommend safety glasses with side shields or chemical goggles to avoid eye contact.

Other protective equipment: Eye wash and safety showers should be readily available.

Hygienic Practices: Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Use of a hand cleaner is recommended. Launder contaminated clothing before reuse. Leather shoes can absorb and allow hazardous materials to pass through. Check shoes carefully after soaking before reuse.

Section 9 - Physical And Chemical Properties

Boiling Range:	262 F (128 C) - 262F (128C)	Vapor Density:	Heavier than Air
Odor:	Solvent	Odor Threshold:	N/D
Appearance:	Pale Yellow Viscous Liquid	Evaporation Rate:	Slower Than Ether
Solubility in H2O:	Reacts		
Freeze Point:	N/D	Specific Gravity:	1.05
Vapor Pressure:	4.9 mmHg at 68F (20C)	PH:	N/D
Physical State:	Liquid		

(See section 16 for abbreviation legend)

Section 10 - Stability And Reactivity

Conditions To Avoid: No Information.

Incompatibility: Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products: Carbon monoxide, nitrogen oxides, and unidentified organic compounds. Consider all smoke and fumes from burning material as very hazardous. Welding, cutting or abrasive grinding can create smoke and fumes. Do not breathe any fumes or smoke from these operations.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

Section 11 - Toxicological Information

Product LD50: N/D

Product LC50: N/D

Chemical Name	CAS Number	LD50	LC50
HOMOPOLYMER OF HDI	28182-81-2	>5000 MG/KG, ORAL, RAT	3124 MG/KG
N-BUTYL ACETATE	123-86-4	7.4 G/KG RABBIT ORAL	>1800 PPM/6H INHALATION

META-XYLENE	108-38-3	NOT AVAILABLE	NOT AVAILABLE
PARA-XYLENE	106-42-3	NOT AVAILABLE	NOT AVAILABLE
ETHYL BENZENE	100-41-4	3500 MG/KG RAT, ORAL	NOT AVAILABLE
ORTHO-XYLENE	95-47-6	NOT AVAILABLE	NOT AVAILABLE
HEXAMETHYLENE DIISOCYANATE	822-06-0	710 MG/KG, ORAL RAT	23 PPM / 4 HRS

Section 12 - Ecological Information

Ecological Information: No data

Section 13 - Disposal Information

Disposal Information: Dispose of in accordance with State, Local, and Federal Environmental regulations. Responsibility for proper waste disposal is with the owner of the waste.

Section 14 - Transportation Information

DOT Proper Shipping Name:	Paint	Packing Group:	III
DOT Technical Name:	N/A	Hazard Subclass:	N/A
DOT Hazard Class:	3	Resp. Guide	128
DOT UN/NA Number:	1263	Page:	

Additional Notes: None.

Section 15 - Regulatory Information

CERCLA - SARA HAZARD CATEGORY

This product has been reviewed according to the EPA Hazard Categories promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD, FIRE HAZARD

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS Number</u>
META-XYLENE	108-38-3
PARA-XYLENE	106-42-3
ETHYL BENZENE	100-41-4
ORTHO-XYLENE	95-47-6
HEXAMETHYLENE DIISOCYANATE	822-06-0

TOXIC SUBSTANCES CONTROL ACT

All components of this product are listed on the TSCA inventory.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(B) Substances exist in this product

U.S. STATE REGULATIONS AS FOLLOWS:

NEW JERSEY RIGHT-TO-KNOW

The following materials are non-hazardous, but are among the top five components in this product.

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

CALIFORNIA PROPOSITION 65

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

Chemical Name
ETHYL BENZENE

CAS Number
100-41-4

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards:

Chemical Name
TOLUENE

CAS Number
108-88-3

INTERNATIONAL REGULATIONS AS FOLLOWS:

CANADIAN WHMIS

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

CANADIAN WHMIS CLASS: B2 D2A D2B

Section 16 - Other Information

HMIS Ratings

Health: 3

Flammability: 3

Reactivity: 1

Personal Protection: X

VOLATILE ORGANIC COMPOUNDS, GR/LTR MIXED (UNTHINNED): See Part A MSDS

REASON FOR REVISION: Changes made in Section(s): 8 and 15

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations