



SONNEBORN SONOLASTIC SL-1 SEALANT

MSDS Number

BBXWJ

National Stock Number

8010-00F007387

Product Name

SONNEBORN SONOLASTIC SL-1 SEALANT

Manufacturer

SONNEBORN BUILDING PRODUCTS

Product Identification

Product ID:SONNEBORN SONOLASTIC SL-1 SEALANT

MSDS Date:01/01/1987

FSC:8010

NIIN:00F007387

MSDS Number: BBXWJ

Responsible Party

SONNEBORN BUILDING PRODUCTS

7711 COMPUTER AVE

MINNEAPOLIS , MN 55435-5402

US

Emergency Phone: 612-835-3434

Info Phone: 612-835-3434

Cage: DO654

Contractor

SONNEBORN BUILDING PRODUTS

UNKNOW

MINNEAPOLIS, MN 55435

(612) 835-3434

Cage: DO654

Ingredients

METHYLENE BIS(4-CYCLOHEXYLISOCYANATE) *97-2*

CAS: 5124-30-1

RTECS: NQ9250000

Fraction By Weight:

ACGIH TLV: 0.054 MG/CUM

GLYCIDOXYPROPYLTRIMETHOXYSILANE, SILANE,

CAS: 2530-83-8

RTECS: VV4025000

Fraction By Weight: 0.33%

DIBUTYLTIN DILAURATE, URETHANE CATALYST

CAS: 77-58-7



RTECS: WH7000000

Fraction By Weight: 0.4%

OSHA PEL0.1 MG/CUM (SN)

ACGIH TLV: 0.1 MG/CUM, SN(SKIN)

ALIPHAATIC NAPHTHA

Fraction By Weight: 4.97%

CHLORINATED PARAFFINS

Fraction By Weight: 2.69%

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: IRRITATION OF THE MOUTH,
THROAT, STOMACH & RESPIRATORY TRACT.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:HEADACHE, NAUSEA, VOMITING, IRRITATION,
COLLAPSE.

First Aid

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR 15 MINS. SKIN: WASH W/SOAP
& WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DON'T INDUCE
VOMITING. GIVE WATER/MILK IF CONSCIOUS & NOT DROWSY. OBTAIN MEDICAL
ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:115F
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:WEAR SCBA & PROTECTIVE CLOTHING. WATER COOL
CONTAINERS.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY RUPTURE/EXPLODE
(DUE TO PRESSURE BUILD-UP) WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:VENTILATE AREA. WEAR APPROPRIATE PROTECTIVE
EQUIPMENT DURING CLEANUP. ELIMINATE SOURCES OF IGNITION. SHUT OFF
SOURCE OF LEAK IF SAFE TO DO SO. DIKE/CONTAIN. ABSORB W/INERT
MATERIAL. SWEEP/SHOVEL INTO CONTAINERS W/LIDS.

Handling

Handling and Storage Precautions:TIGHTLY RESEAL ALL PARTIALLY USED
CONTAINERS. USE ONLY W/ADEQUATE VENTILATION. STORE AWAY FROM
SOURCES OF IGNITION.
Other Precautions:DON'T TAKE INTERNALLY. AVOID CONTACT W/EYES,
SKIN/CLOTHING. AVOID BREATHING VAPOR/DUST/MIST WASH THOROUGHLY
AFTER HANDLING.

Exposure Controls

Respiratory Protection:IF TLV IS EXCEEDED, USE NIOSH-APPROVED
RESPIRATOR.
Ventilation:LOCAL EXHAUST: TO KEEP BELOW TLV.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GOGGLES
Other Protective Equipment:EYE WASH & SAFETY SHOWER. CLEAN PROTECTIVE
CLOTHING.
Supplemental Safety and Health

Chemical Properties



Vapor Density: > 1
Spec Gravity: 1.1
Evaporation Rate & Reference: SLOWER THAN N-BU AC
Solubility in Water: SLIGHT
Appearance and Odor: LIGHT GREY VISCOUS LIQUID W/SOLVENT ODOR.
Percent Volatiles by Volume: 6.54

Stability

Stability Indicator/Materials to Avoid: YES
STRONG BASES/OXIDANTS. STRONG LEWIS/MINERAL ACIDS.
Stability Condition to Avoid: SOURCES OF IGNITION.
Hazardous Decomposition Products: ACRID SMOKE/COX/ALDEHYDES/ACIDS/TRACES
OF HYDROGEN CYANIDE.
Conditions to Avoid Polymerization: CONTAMINATION WITH WATER.

Disposal

Waste Disposal Methods: DISPOSE OF IAW/FEDERAL, STATE & LOCAL
REGULATIONS. PREVENT WASHINGS FROM ENTERING WATERWAYS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.