



WRITTEN MANLIFT TEST

Name: _____

Date: _____

1. Who may operate a manlift?
 - A. Any journeyman
 - B. Any supervisor
 - C. Any trained and authorized employee
 - D. Anyone that has run one previously

2. How often shall the manlift be inspected?
 - A. Daily
 - B. Weekly
 - C. Monthly

3. When should the manlift be shut down?
 - A. When a malfunction occurs
 - B. When the safety dept. inspects it.
 - C. After receiving you supervisors permission
 - D. Only if a malfunction prevents the machine from working

4. The operator and all passengers in the basket must wear a harness and lanyard. This is a?
 - A. Haskell rule
 - B. OSHA/WISHA rule
 - C. Client rule
 - D. All of the above

5. What is the maximum grade that the lift can be safely operated on?
 - A. 1% (one inch rise in ten feet)
 - B. 5% (five inch rise in ten feet)
 - C. 10% (one foot rise in ten feet)

6. What is the minimum distance that must be maintained between any part of the manlift and an energized electrical power line?
 - A. 5 feet
 - B. 10 feet
 - C. 20 feet
 - D. 50 feet

HASKELL CORPORATION MANLIFT TEST

7. When using the manlift as a crane, how and where should the load be attached?
- A. The basket should be removed and attached to the pins.
 - B. A shackle should be used to hang the load from the center of the basket.
 - C. A pad eye should be welded on the end of the boom near the basket.
 - D. Never under any conditions should the manlift be used as a crane.
8. What functions are controlled by the platform foot or dead man switch?
- A. All ground and platform controls
 - B. The ground controls.
 - C. All platform controls.
 - D. The foot switch engages the starter.
9. When travelling from work area to work area the boom should?
- A. Be raised six to ten feet to allow the operator an unobstructed view.
 - B. Always be centered over the rear axle and raised only high enough to clear the terrain and allow a clear view.
 - C. Should always be centered over the front axle to allow the operator an unobstructed view.
 - D. Should always be placed at an angle to either side to offer an unobstructed view.
10. The manlift is insulated against electrical currents and may be used on or in the proximity of live electrical lines.
- A. True
 - B. False
11. Ground personnel should not be allowed to work under the elevated manlift
- A. True
 - B. False
12. When entering and exiting the manlift at an elevated position, it is necessary to have an operator remain in the basket.
- A. True
 - B. False
13. Ground personnel working in the area should be trained to utilize the ground controls in case of an emergency.
- A. True
 - B. False
14. Platform capacity does not include the operator.
- A. True
 - B. False

HASKELL CORPORATION MANLIFT TEST

15. If additional reach is needed, planks may be placed on the mid rail, or the top rail.
- A. True
 - B. False
16. When traveling on a steep grade, the basket should be placed against the ground and the boom should be extended to help push the manlift up the steep grade.
- A. True
 - B. False
17. When working at an elevated position in the manlift it is necessary to have the work area below flagged off.
- A. True
 - B. False

Employee's signature

Examiner's signature

Date: _____

Date: _____

Score: _____